

Börresen Cooltech AS Postboks 130 Holmlia 1203 Oslo Norway	Your order 36461	
	Our reference 114555	Packing slip / Date PS516890 21.4.2016
	Your reference Lasse Djupvik	

Item	Product , Grade and Size			
001	Cupori 210 Ref kopparrör EN 12735-1 Cu-DHP R220 i ring 9,52X0,81 MM X 15 M	154.52 Kg 780.00 M		PU114555.1
002	Cupori 210 Ref kopparrör EN 12735-1 Cu-DHP R290 15,88 (5/8)X1,02 MM X 5 M Nitrogenfyllda	681.12 Kg 1600.00 M		PU114555.2
003	Cupori 210 Ref kopparrör EN 12735-1 Cu-DHP R290 12,7 (1/2)X0,89 MM X 5 M Nitrogenfyllda	369.00 Kg 1250.00 M		PU114555.3
004	Cupori 210 Ref kopparrör EN 12735-1 Cu-DHP R290 22,23 (7/8)X1,14 X 5 M Nitrogenfyllda	742.72 Kg 1100.00 M		PU114555.4

According to: EN 12735-1

Mechanical properties

Item	Tensile strength R _m N/mm ²	0.2 % proof strength R _{p0.2} N/mm ²	Elongation %		Hardness	Grain size mm
001	261	102	A5	54		0,015
002	472	438	A5	7		
003	466	431	A5	8		
004	465	435	A5	6		

Chemical composition %
 Cu-DHP/CW024A
 Cu min 99,90
 P 0,03

EDDY CURRENT TESTED:100%

Electrical conductivity at 20 ° C % IACS (mass), annealed

We hereby certify, that the material described above complies with the order.



Katja Silvanto

This document has been printed out through electrical mail.
 A copy with original signature is available in our factory.

These products have been produced under a certified Quality System
 ISO 9001: 2008 / DNV Certificate No.80561-2010-AQ-FIN-FINAS

Cupori Oy

P.O. Box 60, FIN-28101, Pori, Finland
 Tel. +358 2 511 4111, Fax +358 2 511 4002
 Domicile: Pori, Finland. Business ID 2639859-8, VAT FI26398598

Börresen Cooltech AS Postboks 130 Holmlia 1203 Oslo Norway	Your order 36461	
	Our reference 114555	Packing slip / Date PS516890 21.4.2016
	Your reference Lasse Djupvik	

Item 005	Product , Grade and Size Cupori 210 Ref kopparrör EN 12735-1 Cu-DHP R290 28,58 (1 1/8)X 1,27 MM X 5 M Nitrogenfylda	379.90 Kg 390.00 M	PU114555.5
-------------	---	-----------------------	------------

According to: EN 12735-1

Mechanical properties

Item	Tensile strength R _m N/mm ²	0.2 % proof strength R _{p0.2} N/mm ²	Elongation %	Hardness	Grain size mm
005	456	419	A5 6		

Chemical composition %
 Cu-DHP/CW024A
 Cu min 99,90
 P 0,03

EDDY CURRENT TESTED:100%

Electrical conductivity at 20 ° C % IACS (mass), annealed

We hereby certify, that the material described above complies with the order.

Katja Silvanto

This document has been printed out through electrical mail.
 A copy with original signature is available in our factory.

These products have been produced under a certified Quality System
 ISO 9001: 2008 / DNV Certificate No.80561-2010-AQ-FIN-FINAS

Cupori Oy

P.O. Box 60, FIN-28101, Pori, Finland
 Tel. +358 2 511 4111, Fax +358 2 511 4002
 Domicile: Pori, Finland. Business ID 2639859-8, VAT FI26398598